
LGMG Diesel - Articulating Boom Lift


SPECIFICATIONS


MODELS	AR11J
Measurements	Metric
Work Height Max.	12.75m
Platform Height Max.	10.75m
Horizontal Outreach	6.78m
Up and Over Height	5.32m
Platform Length	1.42m
Platform Width	0.76m
Stowed Length	5.77m
Length-Transport (jib tucked)	4.46m
Overall Width	1.85m
© Stowed Height	2.06m
Height-Transport	2.29m
• Wheelbase	1.88m
Ground Clearance	0.19m
PRODUCTIVITY	
Max. Platform Occupancy	2
Platform Capacity	270kg
Turntable Rotation	355°
Drive Speed-Stowed	5km/h
Drive Speed-Raised	0.8km/h
Gradeability	45%
Max. Wind Speed	12.5m/s
Turning Radius-Inside	2.6m
Turning Radius-Outside	4.7m
Max.Slope	3°/4.5°
Tires Type	Foam-filled non-marking
Tires Models	10-16.5
POWER	
Power Source	Kubota D1105 18.2kW
Fuel Tank Capacity	40L
HYDRAULIC SYSTEM	
Hydraulic Oil Volume	58L
WEIGHT	
Machine Weight	5,400kg

STANDARD FEATURE	S
Proportional control	Foam-filled non-marking tires
Horn/Hour meter	Platform control cover
Emergency stop device	Overload sensing system
Auto-leveling platform	Intelligent diagnostic system
Anti-collision protection	Oscillating axle
Full-height drive	Telematics connector
Flashing beacons	Over tilt protection system
Cylinder bellows	Battery isolator switch (double pole)
Squawker alarm	Start motor isolator switch (double pole)
Half-height mesh platform	

OPTIONAL	
AC power to platform	RT Foam-filled tires
Telematics	Solid tires
Auxiliary rail	Solid non-marking tires
Platform tool box	Biodegradable hydraulic oil







Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only. This model is only available for the Australian market.

LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel: +86 531 6787 9283

LGMG Machinery Australia Pty Ltd

Address: 27 Broadhurst Road, Ingleburn, NSW 2565 Email: kevan.jarvis@lgmg.com.cn Tel: +61 499 685 544

